

THE CLAIMS:

The status of the claims is as follows:

1. (Previously Amended) A disk device comprising:

a disk drive including a head for reading data written to a disk and a processing circuit for processing the data; and

a host computer connected to said disk drive through an interface;

wherein the processing circuit of said disk drive includes a low-level error-correction code unit for performing error correction of the data written to a physical address corresponding to a single sector of the disk; and

the host computer includes a high level error correction code unit for performing error correction of the read data supplied through the interface and read from more than one sector of the disk.

2. (Original) A disk device according to claim 1, wherein:

a high-reliability disk to which both a low-level error-correction code and a high-level error-correction code are written and a disk to which only the low-level error-correction code is written are loadable into said disk drive;

when the high-reliability disk is loaded, the processing circuit of said disk drive performs low-level error correction, and then said host computer, to which the correction data is supplied, performs high level error correction; and

when the latter disk is loaded, the processing circuit of said disk drive performs low-level error correction, and said host computer processes the corrected data.

3. (Original) A disk device according to claim 1, wherein:

information is written to the disk for discriminating a high-reliability disk to which both a low-level error-correction code and a high-level error-correction code are written from a disk to which only the low-level error correction is written ; and

said host computer determines which disk is inserted based on the information.

4. (Currently Amended) A storage device comprising:
a low-level error correction unit within a drive configured to detect, and when necessary, correct errors on the fly in data written to a single sector comprising 512 bytes of a storage area of a disk;
a read mechanism coupled to the low-level error correction unit; and
a host coupled to the drive comprising a high-level error correction code unit configured to detect, and when necessary, correct errors on the fly in data stored in more than one sector of the storage area of the disk.

5. (Previously Added) The storage device of claim 4 wherein the low-level error correction unit detects and, when necessary, corrects an error in the data storage area that corresponds to a physical address.

6. (Previously Added) The storage device of claim 5, wherein the high-level error correction code unit detects and, when necessary, corrects an error in the data storage area that corresponds to a plurality of physical addresses.

7. (Previously Added) The storage device of claim 4, wherein the high-level error correction code unit detects and, when necessary, corrects an error in the data storage area that corresponds to a plurality of physical addresses.

8. (Previously Added) The storage device of claim 4 wherein both the drive and the host are configured to detect and, when necessary, correct errors in data in a common sector.

9. (Currently Amended) The storage device of claim 4 wherein the read mechanism comprises a read/write mechanism.